



The Refrigeration Experts

Product specification



MBCT75: 75kg Modular Blast Chiller

17-121

Floorless modular blast chiller with 700mm door width

About the product

High capacity Modular Blast Chillers from the Refrigeration Experts allow bulk rapid chilling without compromising food safety or quality.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#)

Learn more about our [Blast Chiller range](#)

Why choose this product

- 75kg chilling capacity 70°C to 3°C in less than 90 minutes within specifications. Entry temperature of up to 90°C for chilling
- Supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase+neutral)
- Doors to the front and rear of the unit allow for loading and unloading from both sides
- Foster Circulair air circulation system ensures uniform chilling whilst protecting the food surface
- Robust modular construction
- Intuitive easy touch control panel - Just press and go with easy to use colour coding to indicate cycle status
- Operator-friendly fans cut-out whenever the blast chiller door is opened

Specification

Technical		Dimensions	
Refrigerant	R404a/449a/452 a	Height (mm)	2350
Electrical supply	230/50/1	Width (mm)	1350
Fuse rating (A)	16	Depth (mm)	1300
Current (A)	4.3	Gross volume (ltr)	75
Power (W)	1080	Chilling capacity (kg)	75
Refrigeration duty (kW)	8850	Gross weight (kg)	790
		Net weight (kg)	749

Build		Energy	
Finish ext/int	White lam & White foodsafefinish	Climate Class	5
Section configuration	Right hinge		
System	Remote		

Footnotes

- Anti Condensation heater to control panel recommended where products are installed in an ambient below 15°C e.g. Prep rooms
- All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase + neutral)

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.